

IntegraTint 7250 (Colorant)

DESCRIPTION

IntegraTint 7250 is a 100% solids colorant designed specifically for use with IntegraCoat Solutions 100% solids epoxy coating systems. It provides excellent color strength and is formulated with highly concentrated pigments. The product contains no solvents, reactive diluents, heavy metals, or chromates.

KEY ADVANTAGES

- High pigment loading for strong, consistent color development
- 100% solids, Zero VOC
- Free of reactive diluents, solvents, heavy metals, and chromates
- Designed for use with IntegraCoat Solutions 100% solids epoxy systems

TYPICAL USES

IntegraTint 7250 is used to pigment body coats, base coats, and other resinous flooring components in IntegraCoat Solutions 100% solids epoxy systems. It is suitable for decorative and functional flooring applications in commercial, industrial, residential, and institutional environments.

IntegraTint 7250 may also be compatible with other coating products, including non-100% solids epoxy systems and other coating chemistries. Compatibility should be evaluated and confirmed through testing prior to use. Contact your IntegraCoat Solutions representative for additional information regarding compatibility with specific products or coating systems.

IntegraTint 7250 is not compatible with water-based products.

TECHNICAL DATA

LIQUID PHASE PHYSICAL PROPERTIES	
Mix Solids (By Volume):	100%
Mixed VOC:	0 g/L
*All tests conducted at 77°F and 50% RH	
Contact your IntegraCoat Solutions representative for additional physical property data.	

MIXING

Select the appropriate package size or measure **IntegraTint 7250** according to the specified colorant loading. Follow the specific product's mixing directions.

Typically, add the required amount of **IntegraTint 7250** to the resin (Part A) and mix until homogeneous. Follow the specific product's mixing directions and ratios. Adding **IntegraTint 7250** to already mixed material is generally not recommended, as it may increase mixing time and reduce working time.

For project-specific information, contact your IntegraCoat Solutions representative.

SHIPPING & PACKAGING DATA

Packaging:	16 oz. jar, 32 oz. jar 1-gallon pail, bulk 3.5-gallon pail
Shelf Life:	12 months, stored indoors at 55–80°F (13–27°C)

SAFETY

Before beginning any work, thoroughly review all applicable Safety Data Sheets (SDS), Product Data Sheets, and equipment manuals. Follow all instructions and safety precautions during storage, handling, surface preparation, and product application.

Improper use can present serious hazards to health and safety, including the risk of fire, explosion, chemical exposure, or respiratory illness. Always wear the appropriate personal protective equipment (PPE) when operating machinery or handling coatings or concrete.

Be especially cautious of concrete dust, which may contain crystalline silica and other hazardous materials that can cause silicosis or other serious illnesses if inhaled.

It is the responsibility of the installation company, general contractor, engineering firm, EPC contractor, and/or facility owner to ensure compliance with all applicable jobsite, local, state, and federal safety regulations.

For further guidance, refer to industry standard AMPP Paint Application Guide No. 10: Guide to Safety and Health Requirements for Industrial Painting Projects.

WARRANTY

IntegraCoat Solutions warrants its products to be free from defects in material and workmanship. IntegraCoat Solutions' sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at IntegraCoat Solutions option, to either replacement of products not conforming to this Warranty or credit to the Buyer's account in the invoiced amount of the nonconforming products.

WARRANTY (CONTINUED)

Any claim under this warranty must be made by the Buyer to IntegraCoat Solutions in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the ship date, whichever is earlier. Buyer's failure to notify IntegraCoat Solutions of such nonconformance as required herein shall bar Buyer from recovery under this warranty.

IntegraCoat Solutions makes no other warranties about the product. No other warranties, whether expressed, implied, or statutory, such as warranties of merchantability or fitness for a particular purpose, shall apply.

Any recommendation or suggestion relating to the use of the products made by IntegraCoat Solutions, whether in its technical literature, or in response to specific inquiry or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for the Buyer to satisfy itself of the suitability of the products for its own particular use and it shall be deemed that Buyer has done so, at its sole discretion and risk. Variation in environment, changes in procedure of use, or extrapolation of data may cause unsatisfactory results.

LIMITATION OF LIABILITY

IntegraCoat Solutions' liability on any claims based upon IntegraCoat Solutions' negligence or strict liability, for any loss or damage arising out of, connected with, or resulting from the use of the products, shall in no case exceed the purchase price allocable to the products or parts thereof which give rise to the claim. In no event shall IntegraCoat Solutions be liable for consequential or incidental damages.

LITERATURE REVISION:

PDS: IntegraTint 7250 (Colorant) - Rev. 260915

Published literature is subject to change without notice. IntegraCoat Solutions is constantly engaged in the testing of existing formulations, the development of new innovative technologies, and the evaluation of the latest practices. The latest literature should always be consulted at www.integracoat.com